

TOP ONE TECH LIMITED

15" LCD Open frame SAW Touch Monitor

(the Water-proof and Compact Type)

Model: TOT150USW001

Part number: TOT150K1S001



Top One Tech's 15" compact open frame LCD touch monitors have a long-lasting product cycle because the enclosure is controlled by Top One Tech's specifications. Future panel improvements are therefore possible without external changes. The TOT150USW001 integrate with the Top One Tech's SAW technology touchscreen.

Features

- Bezel seal standard: NEMA3 and IEC IP65
- Long lasting product cycle-enclosure controlled by Top One Tech specifications
- Future generation panels phased-in without external changes
- High quality panel with high brightness,high contrast ratio and broad viewing angle
- Multiple mounting options including VESA mount, horizontal or vertical bracket-mount
- Compact and slim profile for easy integration from side,top and bottom
- Top One Tech's SAW technology on pure glass for the ultimate in image quality
- Finger or gloved hand operation
- Dual USB/Serial touch interface port
- Dual VGA/DVI input video format
- Worldwide agency approvals


Specification

Model No.	TOT150USW001	
Series	OT, Water-proof and Compact	
LCD Type	15 " Active matrix TFT-LCD	
Active Area	304.1×228.1mm	
Monitor Dimensions	336.4×264.4×45.9mm	
Suggested Resolution	1024×768	
Support Colors	16.2M	
Brightness(Typ.)	Pure LCD Panel	300cd/m ²
	With SAW Glass Sensor	275cd/m ²
Response Time(Typ.)	5ms	
Viewing Angle (Typ.at CR>10)	Horizontal(left/right)	80°/80°
	Vertical(up/down)	80°/80°
Contrast Ratio(Typ.)	500:1	
Video Input	Dual Analog RGB and DVI video format	
Frequency (H/V)	30~80KHz / 60~75Hz	
Power Supply	Type: External brick	
	Input (line) voltage: 100-240 VAC, 50-60 Hz Output voltage/current: 12 volts at 4 amps max	
Environment	Operating Temp.	0~50°C
	Storage Temp.	-20~60°C
	Operating RH:	20%~80%
	Storage RH:	10%~90%

MTBF	50,000 Hours	
LCD Back light Life(Typ.)	50,000 Hours	
Weight (N.W/G.W)	3.5Kg(1pcs net weight) / 11Kg (2pcs package)	
Package Dimension	429×183×356mm(2pcs per carton)	
Power Consumption	40W Max.	
Mount Interface	1)VESA 75mm and 100mm 2)Mount bracket, horizontal or vertical (Standard mount brackets are supplied)	
OSD Control	Buttons	AUTO,+,POWER,-,MENU
	Function	Brightness, Contrast Ratio, Auto-adjust, Phase, Clock, H/V Location, Languages, Function, Reset
Touch screen Type	Top One Tech 15" SAW 4mm compact touch sensor, anti-glare is optional	
Touch System Interface	Having USB and Serial(RS232) interface	
Touch Response time	USB/Serial: 8.4/10.4ms	
Agency Approval	FCC, CE, RoHS	
Regular Warranty	1 year	

NOTE:The display SPEC. will change follow the relevant LCD panel brand and model

Mechanical Dimensions



Accessories

Power Cable: A North American power cable or an European power cable is included according to the end user's area.

Power Supply Brick: A power supply brick is included.

Touch/Video/DVI Cables: Detachable serial or USB touch cable , video cable and DVI cable are included

L-brackets: Four standard L-brackets are included.

Typical Application

Gaming/Casino Systems
Outdoor and indoor Kiosks
Entertainment
Transport and Ticketing
Hospitality
Banking
Customized Solutions

How to contact us

TOP ONE TECH LIMITED

Mobile Phone : (+86) 13631610695

Tel: 0086-0755-21070641

Whatsapp/Wechat : +8613631610695

Email : sales@toponetech.cn

Skype : elsieyu-sz@hotmail.com

Office in China : Room 512 & 517, Taiyangneng Guigu Building Zhongxing Xiaoqu, Yunfeng Road No.3 Gaofeng shequ, Longhua District, Shenzhen, China

Facilities in China : No. 2, Guihua Jiayi Industrial district, Guanlan, Longhua, Shenzhen, China 51804