

Top One Tech LIMITED

22" LCD Open Frame PCAP Monitor

(PCAP ,LED backlight)

Model: TOT220UCA001

Part number:TOT220K1C001



Top One Tech's 22" open frame LCD touch monitors have a long-lasting product cycle because the enclosure is controlled by Top One Tech's specifications. Future panel improvements are therefore possible without external changes. The TOT220UCA001 integrate with the Top One Tech's PCAP technology touchscreen.

Features

- Bezel seal standard: Zero-bezel, True flat
- Long lasting product cycle-enclosure controlled by Top One Tech specifications
- Future generation panels phased-in without external changes
- High quality panel with high brightness, high contrast ratio and broad viewing angle
- Multiple mounting options including VESA mount, horizontal or vertical bracket-mount
- Compact and slim profile for easy integration from side, top and bottom
- Top One Tech's PCAP technology on pure glass for the ultimate in image quality
- Finger or gloved hand operation
- USB touch interface port
- VGA/DVI input video format
- Worldwide agency approvals


Specification

Model No.	TOT220UCA001	
Touch screen Type	Projected Capacitive touch sensor, 10 points in win7	
Bezel Color	Black	
Diagonal Size	22" diagonal	
Aspect Ratio	16:10	
Dimensions	500*328.4*51.9(mm)	
Active Display Area	473.76*296.1(mm)	
Suggested Resolution	1680*1050@60Hz	
LCD Technology	Active matrix TFT LCD with LED back lighting	
Support Colors	16.7M	
Brightness(Typ.)	LCD Panel	250 nits
	With PCAP	212.5nits
Response Time(Typ.)	5ms	
Viewing Angle (Typ.at CR>10)	Horizontal(left/right)	85°/85°
	Vertical(up/down)	80°/80°
Contrast Ratio(Typ.)	1000:1	
Video Input	VGA ,DVI	
Power Supply	Type: External brick	
	Input (line) voltage: 100-240 VAC, 50-60 Hz	
Environment	Operating Temp.	0~50°C
	Storage Temp.	-20~60°C

	Operating RH:	20%~80%
	Storage RH:	10%~90%
MTBF	40,000 Hours demonstrated	
Weight (Approx.)	Unpacked: 10.5kg; double-packed: 22 kg	
Mount Options:	Side snap installation	
On-Screen Display (OSD)	Accessible through switches on the unit's tethered OSD Control box. Controls :Menu,Up,Down,Select;Settings: Brightness,Contrast,Clock,Phase,H-position,V- position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, OSD H-Position, OSD;V-Position, Recall Defaults, Video Source;Languages:English,French,Italian,German,Spanish,Simplified Chinese, Traditional Chinese, Japanese; Lockouts: OSD, Power	
Agency Approval	CCC,ETL,FCC,CE,RoHS	
Regular Warranty	1 year	

NOTE:The display SPEC. will change follow the relevant LCD panel brand and model

Mechanical Dimensions



Accessories

Power Cable: A North American power cable or an European power cable is included according to the end user's area.

Power Supply Brick: A power supply brick is included.

Touch/Video/DVI Cables: Detachable serial or USB touch cable, video cable or DVI cable are included

L-brackets: Four standard L-brackets are included (option by different model)

Typical Application

Information Kiosk
Banking ATM
Casino Gaming machine
Industrial Control
Transportation
Education and Training

How to contact us

TOP ONE TECH LIMITED

Mobile Phone : (+86)13631610695

Tel: 0086-0755-18070641

Whatsapp/Wechat :+8613631610695

Email : sales@toponetech.cn

Skype : elsieyu-sz@hotmail.com

Office in China : Room 1517, Taiyangneng Guigu Building Zhongxing Xiaoqu, Yunfeng Road No.3

Gaofeng shequ, Longhua District, Shenzhen, China

Facilities in China : No. 2, Guihua Jiayi Industrial district, Guanlan, Longhua, Shenzhen, China 518110